



## Key Features:

- Up to EI240 Fire Rating
- Compressible up to 50%
- Available to suit all common gap sizes
- Accepts joint movement
- No additional sealants required

**TENMAT's** FF108 Linear Gap Seals are fully intumescent linear firestop seals tested to the latest EN Standards. The durable seals are installed under compression and can accept up to 50% movement. They are equally suited to both vertical and horizontal joints. The seals offer up to 4 hour (EI240) fire rating for joints in fire rated walls and floors.

## Availability and Fire Rating

### 1 Seal Required

Seal Size	Min. Gap	Max. Gap	Fire Rating: Floors	Fire Rating: Walls
15x15mm	7.5	13	EI240	EI240
25x20mm	13	22	E240/EI30	E240/EI30
40x20mm	22	35	E240/EI30	E240/EI30
60x45mm	35	50	E240/EI45	E240/EI45
85x45mm	50	70	E240/EI45	E240/EI45
120x60mm	70	100	E240/EI45	E240/EI45

Seal Size	Min. Gap	Max. Gap	Fire Rating: Floors	Fire Rating: Walls
30x15mm	15	25	E240/EI180	E240/EI180
25x20mm	13	22	E240/EI180	E240/EI120
40x20mm	22	35	E240/EI180	E240/EI120
60x40mm	35	50	E240/EI180	E240/EI120
85x40mm	50	70	E240/EI180	E240/EI120
120x50mm	70	100	E240/EI180	E240/EI180

Where 2no. Seals are required, they should be spaced 50mm apart.